



Ladder Frame Tower

It is available in two widths: **SINGLE WIDTH 0.7M WIDE** and **DOUBLE WIDTH 1.35M WIDE**

Both single and double width ladder frames are available in three, four and five rung sizes to provide maximum platform options.

The tower comprises the minimum possible multi-purpose components, no separate ladders or guardrail frames are necessary.

All frames can be used as uppers or lowers simply brace your platform on the third rung below the top of the tower and the correct guardrail height is achieved.

Ladder Frame Tower Features:

- Multi-start Square threaded adjustable legs, incorporating full nut for maximum security.
- The heavy duty splined spigot designed for maximum strength and rigidity and ease of tower assembly.
- The unique ten-impression crimped joint, specially designed to improve resistance to abuse, and reduce repair costs.
- Brace hook assembly, incorporating double torsion stainless steel spring for durable and reliable use.
- Platforms incorporating bolted hook extrusion for easy low cost reparability and platform profile designed to provide minimum deflection and improved strength.

The Euro Towers Ladder frame tower is approved to TUV BSEN 1004 European standard.



Tel: 0047 51 56 49 41

Mob: 0047 47 40 98 37

Email: office@westech.no

Westech AS Dusavikveien 79,
4007 Stavanger, Norway

WESTECH AS